

MILD HBOT CHAMBERS — LYING TYPE



Features

- 1.3 ATA operating pressure
- 3 zipper seal with silicon inlay for tight seal
- Large viewing windows for sufficient ambient light inside chamber
- Nylon protection cover for chamber to protect against damage and dirt and easy to wash
- Emergency valve to speed up depressurisation when required
- Easy operation for self treatment purposes
- High pressure oxygen concentrator delivers 93± 3% oxygen under pressure via a cannula or oxygen mask.
- Internal metal frame holds shape and shortens pressurisation time
- Air compressor and cooler delivers filtered, clean and chilled air into the chamber.

COMPONENTS	FEATURES	SOLO	SOLO PLUS	MID	DUO
CHAMBER	PRICE (Incl VAT)	R159 900	R189 900	R169 900	R179 900
	Pressure	1.3 ATA	1.45 ATA	1.3 ATA	1.3 ATA
	Size	70 x 220 cm	70 x 220 cm	80 x 220 cm	90 x 220 cm
	Weight	12kg	12kg	13kg	14kg
AIR COMPRESSOR	Size	39x 24x 26 cm			
	Type	Oil and grease free. Super absorbent activated carbon filters in both air input and output			
AIR CHILLER	Type	Air drying. Reduces temperature by 7 to 10 degrees			
OXYGEN CONCENTRATOR	Size	35x 32x 57 cm			
	Flow Rate	10 litres p/m			
	Technology	PSA molecular sieve technology. Continuous oxygen production at 93± 3% .			
CHAMBER MATERIALS	DESCRIPTION	DETAILS		PARAMETERS	
CHAMBER	3 layers high strength thermoplastic polyurethane coated dacron	Thickness 1.0mm		Tensile strength Warp: 5500N/5CM(±5) Weft: 4400N/5CM(±5)	Tear strength Warp: 500N/5CM(±5) Weft: 400N/5CM(±5)
WINDOW	Clear thermoplastic polyurethane	Thickness 4.0mm		Tensile strength (MPa) MD: 55.3 CD: 51.1 Hardness: 92A	Tear strength (kgf/cm) MD: 158.0 CD: 154.7 Melting point: 176C
ZIPPER	YKK brand	Zinc alloy		Double head	