

MILD HBOT CHAMBERS — SEATED TYPE



Features

- 1.3 ATA operating pressure
- 3 zipper seal with silicon inlay for tight seal
- Large viewing windows for sufficient ambient light inside chamber
- Full nylon protection cover to prevent damage and dirt, easy to clean
- Emergency valve to speed up depressurisation when required
- Easy operation for self treatment purposes
- High pressure oxygen concentrator delivers 93± 3% oxygen via mask or cannula
- Internal metal frame holds shape and shortens pressurisation time

COMPONENTS	FEATURES	SEATED	SEATED PLUS	
CHAMBER	PRICE (incl vat)	R177 900	R187 900	- Air compressor and cooler delivers clean, filtered and cooled air into the chamber. - Holds fully adjustable lounging chair for extra comfort
	Pressure	1.3 ATA	1.3 ATA	
	Size	110 x 70 x 170 cm	110 x 70 x 220 cm	
	Weight	13kg	14kg	
AIR COMPRESSOR	Size	39x 24x 26 cm		
	Type	Oil and grease free. Super absorbent activated carbon filters in both air input and output		
AIR CHILLER	Type	Air drying. Reduces temperature by 7 to 10 degrees		
OXYGEN CONCENTRATOR	Size	35x 32x 57 cm		
	Flow Rate	10 litres p/m		
	Technology	PSA molecular sieve technology. Continuous oxygen production at 93± 3% .		
CHAMBER MATERIALS	DESCRIPTION	DETAILS	PARAMETERS	
CHAMBER	3 layers high strength thermoplastic polyurethane coated dacron	Thickness 1.0mm	Tensile strength Warp: 5500N/5CM(±5) Weft: 4400N/5CM(±5)	Tear strength Warp: 500N/5CM(±5) Weft: 400N/5CM(±5)
WINDOW	Clear thermoplastic polyurethane	Thickness 4.0mm	Tensile strength (MPa) MD: 55.3 CD: 51.1 Hardness: 92A	Tear strength (kgf/cm) MD: 158.0 CD: 154.7 Melting point: 176C
ZIPPER	YKK brand	Zinc alloy	Double head	